



SA169 SA169A SA169B SA189 SA199
1964-1970 REAR SEAT DIVIDERS

INSTALLATION KIT

- (1) CLEAR SILICONE TUBE**
(24) #8 SELF DRILLING SCREWS
WAIVER:

**WE MAKE NO CLAIM THAT THAT THIS PRODUCT IS A FIRE BLOCK OR A
FIRE PREVENTION PRODUCT OF ANY KIND**

It is recommended this product be primed and painted with rust prohibitive products prior to installation.

- 1) Remove rear seat bottom by pushing seat towards back of car and then lift upwards.
- 2) Remove any screws holding back seat at bottom. Then remove seat back by lifting upwards.
- 3) Remove the screws holding the interior quarter panels in place and then remove panels.
- 4) Remove the cardboard or felt seat divider behind the seat.
- 5) Place new seat divider where the old one was located. It may be necessary to trim the rectangular notches in the new divider.
- 6) Remove divider Using clear silicone; put a bead around the outer edge and in locations where the divider comes into contact with the frame. Allow sealant to cure its proper time as specified on the tube. The sealant reduces vibration of metal to metal during driving.
- 7) Put the seat divider back into desired position. Mark and drill holes approx every 8-10 inches. A 1/8" drill bit should be used for the #8 screws.
- 8) Reinstall rear quarter panels and the rear seat.

**WE ASSUME NO LIABILITY FOR DAMAGE, INJURY OR DEATH
RESULTING FROM THE INSTALLATION OF THIS PRODUCT**